

6U VME USB DVD with Fixed Drive Module



RRT-6U-VME-USB- DVD-F

The 6U VME USB drive module provides support for both a DVD drive and a fixed USB SSD or hard drive

Modes of operation include DVD-ROM, DVD-R/W, CD-ROM and CD-R/W.

USB compliant interface.

FEATURES INCLUDE

- USB interface to front panel
- Provides removable boot disk and/or storage
- Compatible with off-the-shelf DVD/CD utility software
- Compatible with all CPUs with a USB controller
- ROHS compliant
- Power supplied from VMEbus; no separate power supply required

Security Options

Several Security Options are available. Erase/destroy options invoked by command or by discrete input.

- Fast Erase sets all locations to set value.
- NSA/CSS Manual 9-12 Erase erases all locations, including bad blocks, then sets all locations to 0x55, and then internal verification is performed reading 1% of capacity confirming data pattern.
- RCC-TG IRIG 106-07 Chapter 10 Erase erases all locations, including bad blocks, then sets all locations to 0x55, then sets all locations to 0xAA, and finally erased.
- Drive Destroy performs erase of all NAND flash including internal SSD firmware, file system and tables, which makes the drive unusable and unreadable.

Ordering Information

RRT-6UVME-USB-DVD-F - FP - MLC - 480GB - FE - UR

USB Interface
FP - Front Panel

Disk Type
SLC - Single Level SSD
MLC - Multi Level SSD
HDD - Hard Disk Drive

Capacity
Any capacity up to 2TB

Options May be left blank

Security Type
FE - Fast Erase
SE1 - NSA/CSS Manual 9-12 Erase
SE2 - RCC-TG IRIG 106-07 Chapter 10 Erase
DD - Drive Destroy

Conformal Coating
UR - polyurethane
AR - acrylic

Example: RRT-6UVME-USB-DVD-F-FP-SLC-30GB-FE
Example: RRT-6UVME-USB-DVD-F-FP-MLC-480GB-UR

6U VME USB DVD Drive w/Fixed Drive Module

Specifications

Performance				
Version	HDD	SSD - SLC	SSD - MLC	DVD
Capacities	Up to 2TB	Up to 480GB	Up to 1TB	Standard CD/DVD
Interface	USB2			
Sector Size	512 bytes			
Reliability				
MTBF – VME Board	3,000,000 hours			
MTBF – HDD	500,000 hours			
MTBF - SSD	1,000,000-3,000,000 hours			
MTBF – DVD	60,000 hours			
Power				
Voltage	+5V +/- 5%			
Watts-idle	2.5W			
Watts-active	5W			
Environmental				
Temperature Operating	5° to 45°C			
Temperature Storage	-20° to 65°C			
Relative Humidity	8% to 80%			
Altitude	10,000 feet 3,000 metres			
Shock – Operating	5 G, 1mS; half sine			
Shock – Non Operating	60 G, 2mS; 200 G, 11mS; half sine			
Vibration – Operating	0.3 G horizontal, 0.2 G vertical, 5Hz to 500Hz to 10Hz, sine swept, 1.0 oct/min			
Vibration – Non Operating	2.0 G (zero to peak), 5Hz to 500Hz to 10Hz, sine swept, 1.0 oct/min			
Physical				
Form Factor	6U VME			
Weight	24oz (681g)			
Pitch	1.0"			

Red Rock Technologies, Inc. reserves the right to modify, change or discontinue specific products within its product line at its own discretion. Red Rock Technologies, Inc. does not assume any liability resulting from the application or use of its products. The information contained herein has been checked and is believed to be entirely accurate, however, no responsibility is assumed for inaccuracies.

"Red Rock Technologies" and the mountain logo are registered trademarks of Red Rock Technologies, Inc.

© Copyright 2016 Red Rock Technologies, Inc. All rights reserved. (Rev. 10/25/2016)