

3U cPCI Removable Compact Flash Module

RRT-CPCI-CF



The cPCI Removable Compact Flash (CF) module is a storage module with a dual channel PCI ATA/IDE controller that supports:

- One Fixed CF
- One Removable CF
- One fixed and one removable CF

Provides boot drive and/or disk storage for 3U cPCI systems. The CF connectors are rated for 10,000 mating cycles to support frequent insertions/removals.

FEATURES:

- PCI 32 bit data at 33MHz per IEEE 1386-2001
- Uses COTS CF drives for a wide range of capacity/speed options
- Current capacities up to 1TB per cPCI module (2 CF drives x 512GB)
- Removable CF secured by rugged retainer clip
- Robust design for high shock & vibration environments
- CF connectors rated for 10,000 mating cycles
- 3.3V and 5V PCI interface compliant
- Compact Flash with write protect switch available
- VxWorks®, Linux and Windows® drivers available
- Front panel activity LEDs
- ROHS compliant

Ordering Information - 3U cPCI Removable Compact Flash Module

RRT-CPCI-CF - **R** - **UR**

Options May be left blank

Port
R - Removable CF
F - Fixed CF
B - 1 Removable/1 Fixed

Conformal Coating
UR - Polyurethane
AR - Acrylic

Example: RRT-CPCI-CF-R-UR
Example: RRT-CPCI-CF-F-UR

Ordering Information - Compact Flash

RRT-CF - **SLC** - **512GB** - **2** - **X** - **WP**

Requirements

NAND FLASH Type
SLC - Single Level
MLC - Multi Level

Capacity in MB or GB
Up to 1TB (2 CF Drives x 512 MB)

Options (may be left blank)

Write Performance
1 - 16MB/s, 2 - 24MB/s, 3 - 33MB/s,
5 - 50MB/s, 6 - 60MB/s

Extended Temperature Range
X - -40°C to 85°C

Write Protect
WP - Write Protect

Example: RRT-CF-MLC-512GB
Example: RRT-CF-SLC-60GB-6-X
Example: RRT-CF-MLC-128GB-2-WP



3U cPCI Removable CF Module Specifications

Performance	
Interface	PCI revision 2.2, 32-bit data at 33MHz
Read/Write	133MB/S
Sector Size	512
Reliability	
MTBF-Drive (1)	3 million
CF Connector Mating cycles	10,000
Power	
Voltage	+5V +/- 5%, +3.3V +/- 5%
Watts-idle	1.2
Watts-active	2.5
Environmental	
Temperature operating	0° to 70°C
Temperature storage	-40° to 85°C
Relative Humidity	5% to 95%
Altitude	80,000 ft (24,000 meters)
Shock	40g
Vibration	0.1g ² /Hz
Physical	
Weight	6.48oz; 184g max
(1) Telcordia SR-322, Issue 3, operating temp (40° C), electrical stress (50%), environmental factor (1.0)	

Red Rock Technologies, Inc. reserves the right to modify, change or discontinue specific products within its product line at its own discretion. Red Rock Technologies, Inc. does not assume any liability resulting from the application or use of its products. The information contained herein has been checked and is believed to be entirely accurate, however, no responsibility is assumed for inaccuracies.

"Red Rock Technologies" and the mountain logo are registered trademarks of Red Rock Technologies, Inc.

© Copyright 2017 Red Rock Technologies, Inc. All rights reserved. (09/07/2017)

206 West Julie Drive - Suite 2, Tempe, AZ 85283 | United States of America

Tel: 480-483-3777 | Toll Free: 1-800-808-7837

www.redrocktech.com | info@redrocktech.com

© Copyright 2017 Red Rock Technologies, Inc.

